

Drivers and card assignments

Configure network drivers, and which interface each card is assigned to. The current configuration is as follows:

```
GREEN : "pci: Intel Corporation Ethernet Connection  
I219-V (rev 21)"  
GREEN : (c8:5b:76:48:ea:4a)  
RED   : "usb: Huawei Technologies Co., Ltd. ME906s LTE  
M.2 Module"  
RED   : ██████████
```

Do you wish to change these settings?

OK

Cancel

Interface - RED

Enter the IP address information for the RED interface.

- Static
- DHCP
- PPP DIALUP (PPPoE, modem, ATM ...)

DHCP Hostname: ipfilte_____

Force DHCP MTU: _____

IP address: 0.0.0.0_____

Network mask: 0.0.0.0_____

Gateway: 0.0.0.0_____

OK

Cancel

PPP setup

Profile

Profile

1. LTE1

Select

Delete

Restore

Connection

Interface:

Modem

Refresh

[Modem configuration](#)

Interface:

ttyUSB0

Monitor Interface:

ttyUSB2

Computer to modem rate:

115200

Number: *

*99#

Modem speaker on:

Dialing mode:

Tone

optional AT command 1

AT+CPIN=

optional AT command 2

optional AT command 3

ISP requires Carriage Return:

Idle timeout (mins; 0 to disable): *

15

Connection debugging:

Reconnection:

Dial on Demand

Persistent

In case reconnection fails, switch to profile:

1. LTE1

Dial on Demand for DNS:

Holdoff time (in seconds): *

30

Maximum retries: *

5

Authentication:

Username: *

tm

Password:

.....

Method:

PAP or CHAP

Script name:

MTU/MRU

MTU:

MRU:

Profile name: *

LTE1

Save

Legend:

* Required field

Modem Information

Modem Hardware

Vendor	Huawei Technologies Co., Ltd.
Model	ME906s-158
Software Version	11.617.04.00.00
IMEI	[REDACTED]
Capabilities	+CGSM, +DS, +ES

SIM Information

IMSI

[REDACTED]

Network Information

Network Registration	NOT REGISTERED, NOT SEARCHING
Network Operator	Telekom.de
Network Mode	LTE
Signal Quality	-71 dBm